

Overview

Product information



Single relay-DRPT-2C-LR-A220-02A(H)-30010000117

small volume, Max current,2 convert contact, bring instruct light ,with test lever,Rated control Voltage: 220VAC, continued current: 8A

Product advantages

- Safe isolation between coil and contacts
- The maximum power of the contact reaches 8A
- With test button

Product certification

Technical data

Product drawing

3D model

coil side

Coil resistance

23114Ω

Environmental data

Ambient temperature (operating)

-40 °C ... +85 °C

Ambient temperature (storage/transport)

-40 °C ... +85 °C

environment humidity

35%~85%RH

Coil side

Rated input voltage UN

220VAC

Typical input current under UN

22mA

Operating voltage

≤75%

Reset voltage	≥10%
Maximum allowable voltage	1.1
Power consumption under rated conditions	0.8VA

Switch part (contact part)

Contact current maximum	8A
Maximum contact voltage	AC240V DC28V
Contact composition	2C
Contact mechanism	single
Contact material	Ag alloy
Contact resistance	≤100mΩ
Action time	<20ms
Reset time	<20ms
Maximum switching frequency (mechanical)	18000 times/h
Maximum switching frequency (rated load)	1800 times/h
Insulation resistance	≥100MΩ
Withstand voltage (between coil and contact)	1500VAC/1min
Withstand voltage (between different pole contacts)	1000VAC/1min
Withstand voltage (between contacts of the same pole)	1000VAC/1min
Shock proof	10G
Vibration resistant	10-55Hz
Electrical life	>1×10 ⁵
Mechanical life	>1×10 ⁷

Standards/Regulations

Standards/Regulations	IEC 61810-1 IEC 60664
insulation	Basic isolation

Protection level	IP50
Pollution level	3
Oversvoltage category	III

Dimension

high	29.2mm
length	29mm
width	13mm

Overview

Test voltage relay coil/relay contact	1500VAC/1min
Test voltage PDT/PDT	1000VAC/1min
Operation mode	100% work factor
Installation location	Arbitrary

Accessories

Business data

Order number	30010000117
Packing unit	
Minimum order quantity	
Products weight (without packaging)	