

Overview

Product information



Relay base-DSRT08A-E3-00A(H)-30020000060

DSRTrelay base,used for2PDTrelay,screw connection

Product advantages

- Plug-in relay socket
- Safe isolation between coil and contacts
- 10A, 2PDTgrade
- Arc partition between adjacent columns
- Anti-touch cover at the top of the screw

Product certification

Technical data

Product drawing

3D model

□

Environmental data

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage / transport)	-40~+65°C

Technical data

Rated voltage UN	300V
Rated current IN	10A
Installation location	Arbitrary
Assembly instructions	DIN35 rail

Connection data 1

Connection name	enter
-----------------	-------

Connection method	Screw connection
Stripping length	7-8mm
screw thread	M3
Cross section of flexible conductor	0.5... 2.5mm ²
Connectable guide cross section AWG	20-14AWG

Connection data 2

Connection name	Output
Stripping length	7-8mm
Cross section of flexible conductor	0.5... 2.5mm ²
Connectable guide cross section AWG	20-14AWG
Connection method	Screw connection

Dimension

length	73.3mm
width	16mm
Depth including bracket	29.5mm

Accessories

Business data

Order number	3002000060
Packing unit	
Minimum order quantity	
Products weight (without packaging)	