DEGSON

Overview

Product information



DGBSC-SG01/4-10050000475

PCB spring terminal blocks,Rated current:32A.Rated voltage（III/2）:450V,pitch:5.6mm,Color:transparent,Contact surface :Tin

Product advantages

- ☑ Rotatable operating handle,easy to operate
- ☑ Suitable for field wiring,saving installation time

Product certification

Technical data

Product drawing

3D model

Connection capacity

Conductor cross section solid	0.2~4mm²
Conductor cross section flexible	0.2~4.0mm²
AWG	24~12AWG
Strip length	12mm

Electrical parameters UL

Rated voltage (B)	600V

Electrical parameters IEC

Rated current	32A

Rated voltage(III/2)	450V

Item properties

Connection method	Push-in spring connection
Pitch	5.6mm
Number of potentials	5
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-2

Mechanical tests

Test Specification	UL1059/IEC60998

Environmental data

Ambient temperature (operation)	-40℃~85℃(depending on derating curve)

Accessories

Accessories

Install accessories	DGBSC-ACC01
Protective board	DGBSC-ACC05
Coding strip	/

Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Business data

Order number	10050000475
Packing unit	100
Minimum order quantity	30
Products weight (without packaging)	5.33