



GREEN Series HMI GL100/GL100E

Product Features:

- Industrial grade CPU, 800MHz, 128M DDR3
- 10.1", high-definition display, 16.77 million true colors;
- The front panel protection level meets IP65 certification requirements;
- Sealing design of buckle for waterproof and oil resistance.



The GREEN series cooperates with configuration software : **Kinco DTools**.

It supports eight languages versions of Chinese, Traditional Chinese, English ,Korean,Germany,Russia, Arabic and Turkey.


The configuration design content supports all fonts installed in computer system.

It supports cloud monitoring. VNC achieves interoperation between HMI and HMI, HMI and PC, mobile phones(or other terminals), supports convenient components such as installment, PDF browsing and operating log records for designing guiding interface.

GREEN Series HMI GL100/GL100E

- Preferred model for 10" general use
- A non-hollow mask is more effective against oil pollution
- Beautiful appearance, ultra-thin body
- High cost-effective



Model	GL100	GL100E	Mechanical Dimensions (Unit : mm)
Performance specification			
Display size	10.1" TFT		
Display area	222.72mm(W)x125.28mm(H)		
Resolution	1024*600 pixels		
Display color	16.7M color		
Display angle of view	70/70/60/70(left/right/up/down)		
Contrast ratio	500:1		
Backlight	LED		
Brightness	400cd/m ²		
Backlight life	More than 30000 hours		
Touch panel	4 line precision resistance network (surface hardness 4H)		
CPU	ARM RISC 32Bit 800MHz		
Storage	256MB NAND Flash Memory+128MB DDR3 Memory		
RTC	Built-in		
Extensible memory	1 USB Host		
Print port	USB Host/serial port		
Ethernet	None	10/100M self-adaption	
Program download	USB Slave(Micro USB)/ U disk	USB Slave(Micro USB)/ U disk/Ethernet	
Communication port	COM0:RS232/RS485/RS422; COM2:RS232		
Electrical specifications			
Input power supply	DC10V ~ DC28V		
Rated power	6W @24V DC		
Allowable loss of power	<3ms		
Insulation resistance	Over 50MΩ@500V DC		
Hi-pot test	500 VAC 1 minute		
Structure specifications			
PCB	none of spraying		
Shell material	Engineering plastic		
Shape size	280mm*193mm*36mm		
Cutout size	261mm*180mm		
Weight	0.9Kg		
Environmental specifications			
Temperature working	0 ~ 50°C		
Humidity working	10 ~ 90%RH (non-condensing)		
Storage temperature	-20 ~ 60°C		
Storage humidity	10 ~ 90%RH (non-condensing)		
Sine vibration test	10 ~ 500Hz, 30m/s ² , X, Y, Z direction/hour		
Cooling mode	Natural air cooling		
Product certification			
Panel protection grade	Conforming to IP65 certification(4208—93)		
CE authentication	EN61000-6-4:2007+A1:2011, EN61000-6-2:2005		
Software			
Configuration software	Kinco DTools V4.1 and above		

